



**MOBI-FF-PWR**  
mobiLink Power Modem  
for FF and HART



**Description:**

Power your HART or Foundation Fieldbus (FF) devices and perform HART or FF communications using USB. Other fieldbus protocols available. Visit our website for more information.

**Features:**

- Compliant FF Host
- Compliant HART Master
- Built-in power supply for HART and FF Transmitters
- Rugged IP54 enclosure
- USB interface
- FF DTM included (for FDT systems)
- HART DTM included (for FDT systems)
- Works with DevCom2000 (for HART)
- Works with DevComFF.Win (for FF)





**PROCOMSOL**

Process Communications Solutions



## Specifications:

### Enclosure

Dimensions 6.9" x 2.9" x 1.3" (175 mm x 74 mm x 32 mm)  
Total Unit Weight 10.2 oz (290 g)  
Protection Class IP 54

### Safety

Isolation 1500 VDC between USB and field device connections

### FF

Standard IEC 61158-2, Type 1: 31.25 Kbit/s, voltage mode  
Input Current 10 mA  
18 mA (with fieldbus voltage > 9.5V)  
Fieldbus Terminator None

### HART

Specifications HART 4, HART 5, HART 6, HART 7, *wirelessHART*  
HART Physical Layer Spec HCF\_SPEC-54

### DTM

Operating System Windows 7 Professional or higher  
DTM not needed for DevCom2000 or DevComFF.Win software

### USB

Specifications USB 2.0  
Power USB port provides power to unit  
Current Draw 100mA

### Connections

FF 4mm banana jacks  
HART 4mm banana jacks  
USB Connector USB Type C

### Environmental

Operating Temperature -20 degC to 50 degC (-4 degF to 122 degF)  
Storage Temperature -40 degC to 85 degC (-40 degF to 185 degF)  
Humidity 0% to 95% (non-condensing)

### Compliances

Certifications EMC, RoHS, WEEE  
See user manual for details

**ProComSol, Ltd**

*Process Communications Solutions*

Phone: 216.221.1550

Toll Free: 877.221.1551

Email: [sales@procomsol.com](mailto:sales@procomsol.com)

Web: [www.procomsol.com](http://www.procomsol.com)