



# MOBI-PWR-FF

mobiLink Power Modem  
for FF and HART®



Power your HART or Foundation Fieldbus (FF) devices and perform HART or FF communications.

## Features:

- Compliant FF Host
- Compliant HART Master
- Power your HART or FF device
- Rugged enclosure to IP54 standard
- USB interface
- FF DTM included (for FDT systems)
- HART DTM included (for FDT systems)
- Works with DevCom2000 (for HART)
- Works with DevComFF (for Foundation Fieldbus)



Connection to FF Device



# PROCOMSOL

Process Communications Solutions



## Specifications:

### Enclosure

Dimensions	6.9" x 2.9" x 1.3" (175 mm x 74 mm x 32 mm)
Total Unit Weight	10.2 oz (290 g)
Protection Class	IP 54

### Safety

Isolation	1500 VDC between USB and field device connections
-----------	---

### FF

Standard	IEC 61158-2, Type 1: 31.25 Kbit/s, voltage mode
Input Current	10 mA
	18 mA (with fieldbus voltage > 9.5V)
Fieldbus Terminator	None

### HART

Specifications	HART 4, HART 5, HART 6, HART 7, HART Physical Layer Spec HCF_SPEC-54
----------------	---

### DTM

Operating System	Windows 7 (32/64), 8 (32/64), 10 (32/64) Not needed for DevCom2000 or DevComFF
------------------	---

### USB

Specifications	USB 2.0
Power	USB port provides power to unit
Current Draw	100mA

### Connections

FF	4mm banana jacks
HART	4mm banana jacks
USB Connector	USB Type C

### Environmental

Operating Temperature	-20 degC to 50 degC (-4 degF to 122 degF)
Storage Temperature	-40 degC to 85 degC (-40 degF to 185 degF)
Humidity	0% to 95% (non-condensing)

### Compliances

Certifications	EMC, RoHS, WEEE See user manual for details
----------------	--

**ProComSol, Ltd**  
*Process Communications Solutions*

Phone: 216.221.1550  
Toll Free: 877.221.1551  
Email: [sales@procomsol.com](mailto:sales@procomsol.com)  
Web: [www.procomsol.com](http://www.procomsol.com)